


General Description

Fiber Termination Box provides a high density wall-mounted solution for next generation networks, which aims to provide and manage maximum numbers of fiber termination in a limited space. It is normally installed outdoor and wall-mounted.



Front View



Back View

Inside View



Physical Parameter

Dimensions (mm) LxWxH	385x320x120 (max 24 ports)
Material	ABS+PC
Color	White
Empty Weight	4kg
Fully Loaded Weight	6.8kg

Features

- ◆ Waterproof design with IP*65 protection level
- ◆ Integrated with splice cassette and cable management tools
- ◆ Manage small and large quantities of fiber with a high packing density
- ◆ Easy to maintain and extend the capacity
- ◆ Fiber bend radius control more than 40mm
- ◆ Suitable for the fusion splice or mechanical splice
- ◆ Capacity of fiber up to 24 ports
- ◆ FC or SC are both available
- ◆ 1*8 or 1*4 PLC Splitter can be installed as an option
- ◆ Efficient cable management
- ◆ Burglar-proof padlock
- ◆ 24 ports cable entrance for drop cable

Standard Configuration

- ◆ Splice cassette and cable management tools
- ◆ Installation nuts and bolts
- ◆ Protective sleeves
- ◆ Hose clamps
- ◆ Rubber seal for cable entrance

Optional Configuration

- ◆ FBT Splitter

ORDERING INFORMATION

EXAMPLE : FTB-ABS-12SCU1

