

**General Description**

Fiber Termination Box provides a high density wall-mounted solution for next generation networks, which aims to provide and manage maximum numbers of fiber termination in a limited space. It is normally installed outdoor and wall-mounted.


**Physical Parameter**

<b>Dimensions (mm) LxWxH</b>	420x320x130 (36&48 ports)
<b>Material</b>	ABS+PC
<b>Color</b>	White
<b>Empty Weight</b>	4.5kg
<b>Fully Loaded Weight</b>	7.3kg

**Features**

- ◆ Waterproof design with IP\*65 protection level
- ◆ Integrated with splice cassette and cable management tools
- ◆ Manage small and large quantities of fiber with a high packing density
- ◆ Easy to maintain and extend the capacity
- ◆ Fiber bend radius control more than 40mm
- ◆ Suitable for the fusion splice or mechanical splice
- ◆ Capacity of fiber up to 48 ports
- ◆ FC or SC are both available
- ◆ 1\*8 or 1\*4 PLC Splitter can be installed as an option
- ◆ Efficient cable management
- ◆ Burglar-proof padlock
- ◆ 48 ports cable entrance for drop cable

**Standard Configuration**

- ◆ Splice cassette and cable management tools
- ◆ Installation nuts and bolts
- ◆ Protective sleeves
- ◆ Hose clamps
- ◆ Rubber seal for cable entrance

**Optional Configuration**

- ◆ FBT Splitter

**ORDERING INFORMATION**
**EXAMPLE : FTB-ABS-36SCU1**
